

# HP65 DS-B

## HP Water Jetting Unit



**JCB 444 TC Tier 3 or  
JCB 430 Tier 5 Engine**

**25lpm at 1000bar**  
(6.6gpm at 14,500psi)

**31lpm at 800bar**  
(8.2gpm at 11,600psi)

**50lpm at 500bar**  
(13.2gpm at 7,250psi)

Refer to the HP65 pump data sheet for alternative performances

HP65 DS-B, diesel driven, skid mounted, High Pressure water jetting unit, suitable for a wide range of applications.

Applications include: surface cleaning, descaling, heat exchanger/pipe cleaning, vessel cleaning, subsea cleaning and more.

### Dimensions

1.8m long x 1.0m wide x 1.9m high  
(71" long x 39" wide x 75" high)

### Weight

980kg  
(2,156lb)

## Features

- HP65 pump
- Stainless steel pumphead, hard wearing plunger, integral gearbox & SAE engine adaptor
- Transducer for display of discharge pressure & automatic over-pressure shutdown
- Burst disc assembly
- Simple auto-shutdown control panel.
- Pump switches for low inlet pressure & high oil temperature
- Polypropylene water tank, boost pump & dual filtration

- Fabrications are grit blasted & powder coated with a zinc rich primer & durable topcoat suitable for use in corrosive environments
- Polypropylene diesel fuel tank

- Spark arresting exhaust silencer
- Chalwyn valve
- Manual control valve
- Casters
- Road trailer

- Alternative engines
- Full range of accessories for all applications.

## Build Options



Rear view

**Hughes Pumps Limited**  
Spring Gardens,  
Washington, West Sussex,  
RH20 3BS  
United Kingdom

**Telephone** +44 (0) 1903 892358  
**Email** sales@hughes-pumps.co.uk  
**Web** www.hughes-pumps.co.uk



Certification number 4257



Manufactured in the UK since 1970

In line with the company's policy of research and development, alterations in design, dimensions and appearance are incorporated from time to time in order to ensure important developments are included at the earliest opportunity. The Company, therefore, reserves the right to alter design, dimensions etc without notice.